

7 in 1, HVAC/Environment meter

Anemometer, CMM/CFM Humidity/Temp. meter

Model : SP-7000

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

7 in 1

HVAC/Environment meter

Anemometer, CMM/CFM Humidity/Temp. meter

Model : SP-7000

FEATURES

- * 7 in 1 professional environment instruments:
1. Air velocity/Temp., 2. Humidity/Temp.,
3. CFM, CMM, 4. Dew point, 5. Wet bulb,
6. Wind chill, 7. Heat index,
- * Tiny bone shape with lightweight and small size case design are suitable for handling with one hand.
- * Wristlet design provides extra protection to the instrument especially for user one hand operation.
- * Low-friction ball bearing mounted wheel design provides high accuracy at high and low air velocity.
- * High precision humidity sensor with fast response time.
- * Built- in microprocessor circuit assures excellent performance and accuracy.
- * Concise and compact buttons arrangement, easy operation.
- * Memorize the maximum and minimum value with recall.
- * °C/°F detection by pressing button on the front panel.
- * Hold function to freeze the current reading value.

GENERAL SPECIFICATIONS

Display	8 mm LCD display
Measurement	1. Air velocity/Temp. 2. Humidity/Temp. 3. CFM, CMM 4. Dew point 5. Wet bulb 6. Wind chill 7. Heat index
Operating Humidity	Max. 80% RH.
Operating Temperature	0 to 50° C (32 to 122° F)
Over Input Display	Indication of "- - - -"
Power Supply	CR 2032 DC 3V battery
Power Consumption	Approx. DC 5 mA
Weight	160g (battery included)
Dimension	HWD 120 x 45 x 20 mm (4.7 x 1.8 x 1.2 inch).
Standard Accessory	Instruction Manual

ELECTRICAL SPECIFICATION (23 ± 5°C)

Air velocity

Unit	Range	Resolution	Accuracy
ft/min	80 to 3937 ft/min	1 ft/min	± 3% F.S. @ F.S. : full scale
m/s	0.4 to 20.0 m/s	0.1 m/s	
km/h	1.4 to 72.0 km/h	0.1 km/h	
MPH	0.9 to 44.7 mile/h	0.1 MPH	
knots	0.8 to 38.8 knots	0.1 knots	
Temp.	0 to 50 °C 32 to 122 °F	0.1 °C 0.1 °F	
Remark : ft/min : feet per minute MPH : miles per hour m/s : meters per second knots : nautical miles per hour km/h : kilometers per hour			

Humidity/Temp.

Unit	Range	Resolution	Accuracy
% RH	10 to 95 %RH	0.1 %RH	< 70% RH : ± 4 %RH ≥ 70% RH : ± (4 %rdg + 1.2 %RH)
Temp.	0 to 50 °C	0.1 °C	± 1.2 °C
	32 to 122 °F	0.1 °F	± 2.5 °F

Ar flow

Unit	Range	Resolution
CMM	0.024 to 36000	0.001/0.01/0.1/1
CFM	0.847 to 1271300	0.001/0.01/0.1/1/10 (x10)/100 (x100)

Dew point Temp.

Unit	Range	Resolution	Remark
°C	-25.3 to 49.0 °C	0.1 °C	* Calculate from the humidity/Temp. value
°F	-13.5 to 120.0 °F	0.1 °F	
Please refer to http://en.wikipedia.org/wiki/Dew_point			

Wet bulb Temp.

Unit	Range	Resolution	Remark
°C	-5.4 to 49.0 °C	0.1 °C	* Calculate from the humidity/Temp. value
°F	22.2 to 120 °F	0.1 °F	
Please refer to http://en.wikipedia.org/wiki/Wet-bulb_temperature			

Wind chill

Unit	Range	Resolution	Accuracy
°C	-9.4 to 44.2 °C	0.1 °C	± 2.0 °C
°F	15.0 to 112.0 °F	0.1 °F	± 3.6 °F
* Wind chill value is effect only when the Temp. value < 15 °C and Air velocity value > 1.4 m/s.			
* Please refer to http://en.wikipedia.org/wiki/Wind_chill			

Heat index

Unit	Range	Resolution	Accuracy
°C	0 to 100.0 °C	0.1 °C	± 2.0 °C
°F	32 to 212 °F	0.1 °F	± 3.6 °F
Pleas refer to http://en.wikipedia.org/wiki/Heat_index			

Effects of the heat index (shade values)

Celsius	Fahrenheit	Notes
27– 32 °C	80– 90 °F	Caution : Fatigue is possible with prolonged exposure and activity. Continuing activity could result in heat cramps
32– 41 °C	90– 105 °F	Extreme caution : Heat cramps, and heat exhaustion are possible. Continuing activity could result in heat stroke
41– 54 °C	105– 130 °F	Danger : Heat cramps, and heat exhaustion are likely ; heat stroke is probable with continued activity
over 54 °C	over 130 °F	Extreme danger : Heat stroke is imminent
Note : Exposure to full sunshine can increase heat index values by up to 8 °C (14°F).		

* Appearance and specifications listed in this brochure are subject to change without notice.

1112-SP7000