

CABLE TESTER

Model : CB-933

ISO-9001, CE, IEC1010



FEATURES

- * Transmitter : 17 alligators, Red x 16 and Black x 1.
- * Receiver : 2 alligators, Red x 1 and Black x 1.
- * To identify & trace up 16 cores in multi-way cable. It can also be connected to metal type of heating & the water supply installation system for this purpose.
- * High impact ABS plastic housing case.
- * LED display, easy operation with clear readout.
- * Wide application for communication cable maintenance, check up...etc.
- * 1.5V AA (UM-3) battery x 4 PCs,



Lutron

LUTRON ELECTRONIC

The Art of Measurement

CABLE TESTER/CABLE IDENTIFIER

Model : CB-933

SPECIFICATIONS		
<i>Transmitter</i>	Display	Two red LED lamps.
	Power	DC 9V battery, Alkaline type, 006P, MN1604 (PP3) or equivalent.
	Power current	2 mA.
	Alligators	17 alligators, green x 16, black x 1 .
	Dimensions	125 x 70 x 26.5 mm (4.9 x 2.8 x 1.0 inch).
	Weight	Approx. 355 g/0.77 LB.
	Housing	High impact ABS plastic.
<i>Receiver</i>	Display	14 mm seven segment LED, 2 digits, one red LED lamp.
	Power	DC 9V battery, Alkaline type, 006P, MN1604 (PP3) or equivalent.
	Power current	33 mA.
	Alligators	2 alligators, red x 1, black x 1.
	Dimensions	125 x 70 x 26.5 mm (4.9 x 2.8 x 1.0 inch).
	Weight	Approx. 355 g/0.77 LB.
	Housing	High impact ABS plastic.
Cable resistance	25 K ohm, max.	
Accessories	Transmitter with 17 cables & alligators 1 PC. Receiver with 2 cables & alligators 1 PC. Operation manual x 1 PC..... 1 PC.	
Applications	To identify & trace up 16 cores in multi-way cable. It can also be connected to heating and the water supply installation system for this purpose.	

OPERATION	
<p>1) At one end of the cable, connect one of the transmitter terminals marked " CH 1 to CH16 " to each core of the cable under test.</p> <p>2) Connect the " COM " reference lead of the transmitter to a core which is the only known one. At the other end of the cable, connect the " COM terminal " (black alligator) of the receiver to the reference lead to which the " COM terminal " (black alligator) of the transmitter is also connected. When the " Input terminal " (red alligator) of the receiver is successively touched on the cores of the cable under test, the relevant number of the way is indicated on the display of the receiver (1-16).</p>	

* Appearance and specifications listed in this brochure are subject to change without notice.